Camera supraveghere PNI DEX82 PTZ Full HD 1080p dome de exterior

*4.5" Total Metal body construction, IP66 rate protection
*1/2.7" CMOS, 2.0 Megapixels, 10X optical zoom
*HD-SDI digital interface output, 1080P high definition image, live transmission, no delay
*OSD menu available
*PWM function, intelligent IR illumination & power consumption is variable, dependant the zoom factory
*IR distance 50M

Specification	
Camera	
Sensor	1/2.7" progressive scan CMOS
Effective pixels	1080P（1080X1920）
Total pixels	2.0 Megapixels
Output Pixel	1920*1080@30fps1920*1080@25fps1280*720@60fps1280*720@50fps
Lens	10X optical zoom f=4.9mm(W) ~ 49mm(T) ±5%
Iris	F1.6 ~F2.8
View of Angle	H：51.8°（W）～5.86°（T） V：39.1°（W）～4.4°（T）
Min. illumination	Color: 0.01 Lux \ B/W: 0 Lux

D/N	IR-CUT
BLC	Auto
WB	Auto
S/N Ratio	>50dB
Dome	
Pan range	360°continuous rotation
Tilt range	0°~93° auto flip 180°
Manual Pan speed	0.02~220°/S
Manual Tilt speed	0.02~100°/S
Preset Points	220
Pattern Scan	4 groups
Guard Tours	4 groups
Guard Points	Max.16 points, dwell time user selectable
Operating temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operation menu	Multiple languages for OSD menu, English, Spanish etc
Pan and Tilt position display	Support
Humidity	≤95% Non Condensing
Power	AC24V ≤3A
Consumption	< 25W
Lightning Protection	Transient voltage 6000V
Video interface output	SDI CVBS
Communication mode	RS485 (+/-)
Connection	Coaxial Cable
Size/Weight	2.7KG（N.W）,.3.4KG（G.W）
Related validation	IP66,CE,FCC,RoHs
IR parameters	
Auto Control IR LED	PWM
Support ambient light detection	IR illumination on 1-15 grades selectable;
LEDs	6pcs
IR distance	up to 50 meters
Support ambient light detection	IR illumination on 1-9 grades selectable;